TECHNICAL DATA SHEET

MED 5501SI

Single-Coated, Duolaminate PU Film with a Soft Silicone Adhesive with 1.6mm/0.06" perforation pattern

MED 5501SI is a single-coated, transparent polyurethane film with a soft silicone adhesive (SSA). The softness, conformability, and the repositionability of the adhesive offers a high degree of user comfort. The 1.6mm/0.06" perforation pattern in the duolaminate construction provides breathability through its perforations, allows for exudate management, and reduces skin maceration. The silicone adhesive side of the roll is supplied with a blue LDPE release liner. The uncoated side is lined with a white cast paper carrier.



TYPICAL APPLICATION

Designed for conversion as a silicone wound contact layer (SWCL) into multi-layered advanced wound care dressings. Application areas also include patient monitoring, wearables and ostomy flanges.

FEATURES AND BENEFITS

- Gentle and soft adhesion to the skin
- Repositionable with minimal pain on removal
- Secure fixation
- Transparent
- Conformable and flexible
- 1.6mm/0.06" perforations allow for exudate and moisture management
- Non irritating, non sensitizing, skin friendly
- Atraumatic removal with minimal epidermal stripping
- EtO sterilizable

Product Construction					
	TYPICAL VALUES*		DESCRIPTION		
CARRIER THICKNESS	1.6 mils	40 µm	Transparent polyether polyurethane film		
ADHESIVE COAT WEIGHT	150 gsm		Soft silicone adhesive designed for medical applications		
RELEASE LINER THICKNESS	4.0 mils	100 µm	Blue LDPE		
SUPPORT WEIGHT	90 gsm		White cast paper		

^{*}Refer to product specifications for material acceptance limits.



TECHNICAL DATA SHEET

MED 5501SI

Single-Coated, Duolaminate PU Film with a Soft Silicone Adhesive with 1.6mm/0.06" perforation pattern

MED 5501SI

Physical Properties [Not intended as specification]					
	TEST METHOD*	TYPICAL VALUES [†]			
SILICONE ADHESIVE COAT WEIGHT	TM043	150 gsm			
SILICONE PEEL ADHESION (POLYCARBONATE PLATE)	TM040	>0.5 N/25 mm			
SILICONE LINER RELEASE	TM020	0.15 N/25 mm			
PERFORATION DIAMETER	TM041	1.6 mm / 0.06"			
TOTAL OPEN AREA	N/A	17.4%			

^{*}Test method information available upon request.

STORAGE AND SHELF LIFE: Two years when stored at 23°C (73°F), 50% relative humidity, out of direct sunlight, in original packaging.

DEFINITIONS: "Avery Dennison Medical" means Avery Dennison Corporation. "Purchaser", "Customer" and/or "User" means the customer of Seller, jointly referred to as "Parties" or individually as "Party". For the purpose of these Conditions, "Products" means goods, all parts, components and services sold by Avery Dennison Medical to Purchaser.

SAFETY: Customers/Users have full responsibility to determine the suitability of Avery Dennison Medical products for applications in their businesses. This includes both safety and biocompatibility assessments. Material Safety Data Sheets (MSDS) will be provided upon request, as well as summaries of components' biocompatibility testing results (ISO 10993), where available. Customers should perform their own assessments on final products in compliance with applicable regulatory requirements.

LIMITED WARRANTY: All statements, technical information and recommendations concerning Products sold or samples provided by Avery Dennison Medical are based upon tests believed to be reliable but do not constitute a guarantee or warranty, and the Purchaser is responsible for determining whether a Product is fit for a particular purpose and for the Product's application. All Products are sold and samples of products are provided with the understanding that the Purchaser has independently determined the suitability of such products for its purposes. Avery Dennison Medical warrants the Products to be free from defects in material and workmanship by the time of the delivery (in other words: the initial date of the shipment). Should any failure to conform to this warranty appear (i) during the time period stated on the specific product specification sheet, or (ii) during the time period on the specific product information literature in effect at time of shipment, or (iii) if not otherwise specified then within one year after the initial date of shipment, then Avery Dennison Medical shall, upon notification thereof and substantiation that the Products have been stored and applied in accordance with the standards set by Avery Dennison Medical, correct such defects without charge to the Purchaser by either suitable repair or replacement in its sole discretion of Avery Dennison Medical plant or at the location of the Products. Such price of repair or replacement shall not exceed the purchase price of the Products upon which the liability is based, and Avery Dennison Medical may in its sole discretion refund the purchase price of the Product in lieu of any repair or replacement. For Customers, all Avery Dennison Medical materials/products described herein are sold subject to the Conditions of Sales to be found on https://medical.averydennison.com/en/home/terms-and-conditions.html, which may be updated from time to time by Avery Dennison and of which a copy is also available on request. This warranty is exclusive and is n

LIMITATION OF LIABILITY: In no event shall Avery Dennison Medical be liable for any incidental or consequential damages, including but not limited to, loss of profit, loss of use of production or loss of capital. The remedies of the Purchaser set forth herein are exclusive and the total liability of Avery Dennison Medical with respect to any contract, or anything done in connection therewith such as the performance or breach hereof, or from the manufacture, sale, delivery, resale, installation or use of products whether arising out of contract, negligence, strict liability, tort or any other legal theory or under any warranty, or otherwise, shall not exceed the purchase price of the products upon which the liability is based.

To learn more about how our material and adhesive science expertise can help drive your next innovation, call us

US: +1 440 534 2600 Belgium: +32 14 40 48 11 Ireland: +353 43 3349586

www.medical.averydennison.com



[†]Refer to product specifications for material acceptance limits.