


aplix® 745

Miniature hook



Description




- Plastic hooks
- Material : 100 % polypropylene
- Methods of attachment : bonding or welding
- Width : from 16 to 500 mm
- Standard colours: white and black
- Intended to be used with a lightweight looped jersey (aplix® 110), a light knitted loop on a film or a nonwoven fabric (aplix® Nalt range)

Key Benefits

- Very thin contact closure (no need for pressure)
- Excellent shear strength
- Customized colours or backing (aplix® 110, non-woven...) on request
- Large possibility of shapes and designs
- Complies with Oeko-Tex® Standard Class 1



Performances

	Tested with aplix® N32		Tested with aplix® 110	
	New state		New state	
 Peel Strength (N/cm) as defined by EN 12 242	1		0.5	
 Shear Strength (N/cm²) as defined by EN 13 780	14		35	
 Traction Strength (N/cm²) as defined by NF G91-103	1.3		3	

NB : The results shown above are average values obtained from 25 mm wide tapes.

Packaging

Widths	16 mm	50 mm	100 mm	500 mm
Reel length	100 lm	100 lm	100 lm	100 lm
Quantity / box	2400 lm	800 lm	400 lm	100 lm
Core inside ø	45 mm	45 mm	76.2 mm	76.2 mm

Shelf life and disposal information

- Stored in original packaging, away from sunlight, humidity and extreme temperatures
- Recyclability : non adhesive product only
- Disposal recommendation : the product must be entrusted to a waste processing company

The information contained in this document is for reference purposes only.
To obtain data suitable for use in technical specification, please contact your APLIX sales representative.